

This is the technical data sheet of the **Ecoflo<sup>®</sup> Coco Fiberglass EC7 model series**. If you have any questions or comments please contact the customer service at **1 800 632-6356**.

### MATERIAL USED

- **Shell:** fibreglass and polyester resin composite;
- **Lid, central support, tipping bucket, distribution plates and sampling device:** plastic;
- **Filtering media:** organic natural fibers.

	EC7-3500-F-CAN	EC7-850-F-USA	EC7-4500-F-CAN	EC7-1250-F-USA	EC7-5250-F-CAN	EC7-1400-F-USA
Total daily flow	3 500 L	850 US gallons	4 500 L	1 250 US gallons	5 250 L	1 400 US gal
Type of disposal	infiltration		infiltration		infiltration	
Type of bottom	open		open		open	
Length (A)	<b>A</b> 3 345 mm (11')		4 175 mm (13' 8")		4,675 mm (15' 4")	
Width (B)	<b>B</b> 2 361 mm (7' 9")		2 361 mm (7' 9")		2 361 mm (7' 9")	
Height (C)	<b>C</b> 1 320 mm (4' 4")		1 320 mm (4' 4")		1 320 mm (4' 4")	
Inlet height (D)	<b>D</b> 970 mm (3' 2")		970 mm (3' 2")		970 mm (3' 2")	
Inlet height (E)	<b>E</b> 350 mm (1' 2")		350 mm (1' 2")		350 mm (1' 2")	
Outlet height (F)	<b>F</b> –		–		–	
Height of filtering media	800 mm (2' 8")		800 mm (2' 8")		800 mm (2' 8")	
Quantity of filtering media	4 m <sup>3</sup> (140 ft <sup>3</sup> )		5.2 m <sup>3</sup> (177 ft <sup>3</sup> )		6 m <sup>3</sup> (212 ft <sup>3</sup> )	
Treatment surface area	5 m <sup>2</sup> (54 ft <sup>2</sup> )		6.5 m <sup>2</sup> (70 ft <sup>2</sup> )		7,5 m <sup>2</sup> (75 ft <sup>2</sup> )	
Weight*	115 kg (250 lb)		135 kg (300 lb)		145 kg (320 lb)	

\* Weights indicated are approximate and not binding (for handling and lifting purposes only).

